Basic Utility Power Supply

Voltage	Current	Power
600 V	2000 mA	400 W

Application Recommended:

- Mini vertical electrophoresis
- Large vertical electrophoresis
- Horizontal electrophoresis
- Mini tank transfer (normal/fast)
- Large tank transfer
- Semi-Dry electrophoretic transfer

Specifications:

1.	Output voltage:	10 – 600 V in 1v steps
2.	Output current:	10 – 2000 mA in 10 mA steps
3.	Output accuracy:	±1%
4.	Output Power:	400W max
5.	Timing:	1 – 999 min fully adjustable
6.	Display:	3-digital LED
7.	Type of output:	Constant voltage or Constant current
8.	Resume function:	Yes, after power failure
9.	Operation conditions:	0-40℃,0-95% humidity
10.	Safety features:	No load detection, sudden load change detection, overload / short circuit protection.
11.	Dimension:	31×24×8 cm (L×W×H)
12.	Weight:	1.5kg
13.	Certificate:	CE

4A High Current Power Supply

Voltage	Current	Power
300 V	4000 mA	400 W

Application Recommended:

- Mini vertical electrophoresis
- Horizontal electrophoresis
- Mini tank transfer (normal/fast)
- Large tank transfer
- Semi-Dry electrophoretic transfer

Specifications:

1.	Output voltage:	10 – 300 V in 1v steps
2.	Output current:	10 – 4000 mA in 10 mA steps
3.	Output accuracy:	±1%
4.	Output Power:	400W max
5.	Timing:	1 – 999 min fully adjustable
6.	Display:	3-digital LED
7.	Type of output:	Constant voltage or Constant current
8.	Resume function:	Yes, after power failure
9.	Operation conditions:	0-40℃,0-95% humidity
10.	Safety features:	No load detection, sudden load change detection, overload / short circuit protection.
11.	Dimension:	31×24×8 cm (L×W×H)
12.	Weight:	1.5kg
13.	Certificate:	CE

Ordering Information

Cat. No.	Product Description
BL-PBU6204	Basic Utility Power Supply 600V / 2000mA / 400W
BL-PB4A3404ss	4A High Current Power Supply 300V / 4000mA / 400W