


## **BIOPREP-BL-18N Ordinary model -56°C**

### **Freeze Dryer Characteristics:**

- Accord with international standards of Green environmental friendly
- True-color Touch Screen, English Interface, display drying curve and history curve;
- Embedded circuit design, 128 M FLASH, can save dozen times Lyophilized data;
- Large opening trap, no coil inside, with samples pre-freeze function
- Imported refrigeration compressor, low noise
- Cold trap and control panel were made by stainless steel, corrosion-resistant, easy to clean
- Transparent Bell type drying room, secure and ocular
- Stainless steel sample holder, common sample plate spacing adjustable
- Small size and easy to operate
- Nitrogen inflation valve within

<b>BIOPREP- BL--18N</b>	<b>Ordinary Model</b>
<b>No-load Temperature</b>	<-56°C
<b>Freeze Area</b>	0.2m <sup>2</sup>
<b>Plate Load Capacity</b>	2L
<b>Ability to Capture Water</b>	8Kg
<b>Vacuum Degree</b>	<10Pa
<b>Temperature range</b>	-56°C-
<b>Machine Dimension</b>	W670×D525×H910+480) mm
<b>Sample Tray Size</b>	4×Φ240mm
<b>Power</b>	1300W
<b>Power Supply</b>	110V/60Hz or 220V/50Hz

<b>Inter layer spacing</b>	70 mm
<b>Cold trap size</b>	Ø300×405 mm
<b>The number of Schering bottles</b>	Ø22: 360
	Ø16: 698
	Ø12: 1320
<b>N.W./ G.W</b>	<b>110KG/140KG</b>
<b>Picture</b>	

**BIOPREP - BL-18N model**